

# FLIR MPX™

MULTI-FORMAT

## ME343S

### 2.1MP HD Fixed Dome Camera



ME343S  
2.1MP HD Fixed Dome Camera

The FLIR 2.1MP HD Fixed Dome Camera uses the latest MPX multi-format technology compatible with popular analog HD formats\* to deliver excellent 1080p picture quality over coax cabling. Ideal for retrofit applications, the camera is compatible with a wide range of analog HD DVRs for maximum flexibility.

#### HD PICTURE QUALITY

*MPX 1080p HD picture quality over existing coax*

- ME343S – 2.1MP HD, 1080p @ 25/30 fps, 1/2.7" CMOS, 3.6mm lens, 80ft / 24m IR

#### MULTI-FORMAT

*Changing video output is made simple through the camera or recorder OSD*

- Compatible with popular analog HD formats\*
- Backwards compatible with Analog DVRs

#### WEATHERPROOF


*Offers installation flexibility, inside or out*

- IP66 weatherproof rated
- -22°F (-30°C) cold climate capable


\*For analog HD format compatibility, please visit [flir.com/security/mpx](http://flir.com/security/mpx)

# Specifications

Camera		ME343S
Imaging Device		2.1 MP HD 1/2.7"
Effective Pixels		1928 (H) x 1088 (V)
Imager Type		CMOS
Image Readout		Progressive Scan
Day / Night		Auto (ICR) / Color / B/W
Mechanical IR Cut Filter		Yes
Min. Illumination		0.1 lux @ F1.2 (Color) 0.01 lux @ F1.2 (B/W)
S/N Ratio		≤39dB
Horizontal Field of View		80° (H) field of view
IR Illumination Distance		80ft (24m) IR Night Vision
IR Wavelength		840~850nm
IR On / Off Control		N
Video Output		BNC (1080p Multi-format / 960H Analog CVBS)
Electronic Shutter Range		1/30~1/100,000
Optical		
Lens Type		Fixed
Mount Type		Board Type
Iris Type		Fixed Iris
Iris Control Type		AIS
Focal Length		3.6mm
Aperture		F2.0
Optical Zoom		N/A
Focus		Fixed
Video		
Frame rates (Maximum)		1080p @ 25/30fps
Wide Dynamic Range		DWDR
Dynamic Range		N/A
Backlight Compensation		BLC / HLC
White Balance		ATW / Manual
Gain Control		Adjustable
Noise Reduction		2D DNR
Smart IR		Yes
Digital Zoom		No
Video Mirroring/Rotation		No
Video Overlay		No
Window Blanking (Privacy)		No
Defog		No
Menu Languages		English, Spanish, Italian, French, Russian, Greek, Simplified Chinese, Korean, Portuguese
Mechanical		
Material		Aluminum Alloy
Product Dimensions (Dia x H)		3.7 x 2.5" 93 x 64mm
Product Weight		0.9lbs / 0.4kg
Electrical		
Analog Video Out (service only)		No
Power Input		12V DC
Power Consumption (maximum)		3.3W
Current Consumption (maximum)		270mA
Additional Features		
Built-in Heater		N/A
Audio I/O		N/A
Alarm I/O		N/A
Environmental		
Storage Temperature		-40°F ~ +140°F / -40°C ~ +60°C
Storage Humidity		Less than 95% RH
Operating Temperature		-22°F ~ +140°F / -30°C ~ +60°C
Operating Humidity		Less than 85% RH
Cold Start Temperature		-22°F / -30°C
Ingress Protection		IP66 Rated
Vandal Resistance		No
Certifications		
Certifications		CE / FCC / RoHS



## Dimensions



## Available Accessories

For latest accessory / mount compatibility visit <http://flir.com/security/cameramounts>

## Ordering Information

ME343S: 8-41430-01841-4

## Package Dimensions

ME343S: 5.2 x 5.2 x 4.5" / 133 x 133 x 115mm

## MARKHAM, ONTARIO

FLIR Systems, Inc.  
250 Royal Crest Court  
Markham, ON L3R 3S1  
Canada  
PH: +1 866.344.4674

## PORTLAND

Corporate Headquarters  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
USA  
PH: +1 866.477.3687

[www.flir.com/security](http://www.flir.com/security)  
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. (Created 07/05/2017) (17-2110-SEC)